

TECHNICAL FEATURES

STARLED5 NX

Product Class (EN 60601-2-41)	I
Power supply	100-240 VAC \pm 10%
Power consumption	75 W
Frequency	50/60 Hz
Light source	LEDs
Average life	50.000 hrs about
Lighting at the centre, Ec @ 100 cm	130.000 lux (160.000 lux optional)
Intensity adjustment	from 5% to 100%
Colour temperature, CCT	4.500 °K
Variable colour temperature	from 3.700 °K to 4.700 °K continuous (optional)
Colour rendering index, Ra	95
Index R _s	> 90
Chromaticity coordinates	x= 0.365 , y= 0.370
Light field size	24 - 33 cm
Focusable working distance	70 - 150 cm
Lighting depth L1+L2 (20%)	114 cm
Lighting depth L1+L2 (60%)	64 cm
Dimensions, weights and further data	
Light head weight	12 Kg
Light head diameter	67 cm
Low ceiling height arm (LCH)	Optional
Handle	Removable and sterilizable
Colour	White RAL 9002

E. & O.E.



ACEM SpA

Medical Company Division

Via della Tecnica 29 - 40050 Argelato

Bologna - ITALY

Ph +39 051 721844 Fax +39 051 721855

info@acem.it www.acem.it



Acem Medical Company is a registered trademark of Acem S.p.A. All rights reserved
ACEM reserves the right to modify the design and specifications contained herein without any prior notice.

Dep.STARLED5NX.EN rev.2016-02