

## TECHNICAL FEATURES

### SOLED15

Product Class (EN 60601-2-41)	I
Power supply	100 – 240 VAC - 50/60 Hz
DC voltage	24 VDC
Power consumption	16 W
Power consumption with Boost function	22 W
Light source	LEDs
Average life	50.000 hrs about
Lighting at the centre, E <sub>c</sub> @ 100 cm	65.000 Lux (85.000 Lux with Boost function)
Light adjustment	0% - 100%
Lighting area surface	63 cm <sup>2</sup>
Colour temperature, CCT	4.500 °K
Colour rendering index, Ra	95
Index R <sub>9</sub>	> 90
Light field dimension d <sub>50</sub> @ 100 cm	12 cm
Light field dimension d <sub>10</sub> @ 100 cm	23 cm
Lighting depth L1 + L2 (20%)	125 cm
Lighting depth L1 + L2 (60%)	98 cm
Light head weight	2,1 Kg
Light head diameter	22 cm
Ceiling pole and arm weight	5,5 Kg – 8,5 Kg
Wall arm weight	4,8 Kg
Trolley weight	23 Kg
Handle	Removable and sterilizable
Colour	White RAL 9002

E. & O.E.



**ACEM SpA**  
**Medical Company Division**  
Via della Tecnica 29 - 40050 Argelato  
Bologna – ITALY  
Ph +39 051 721844 Fax +39 051 721855  
info@acem.it www.acem.it



Acem Medical Company is a registered trademark of Acem S.p.A. All rights reserved  
ACEM reserves the right to modify the design and specifications  
contained herein without any prior notice.

Dep. SOLED15.EN rev.2016-01